

Türkiye'nin Güvenlik Çözüümü





Double Glass Teknolojisi



3039B Long Distance Waterproof IR Camera



3036B Long Distance Waterproof IR Camera



3031F Waterproof IR Camera



3033D Waterproof IR Camera

TEKNİK ÖZELLİKLER

MODEL	SP 3039B	SP 3036B	SP 3031F	SP 3033D
Görüntü Sensörü	1/3" Sony SUPER HAD CCD	1/3" Sony SUPER HAD CCD	1/3" Sony SUPER HAD CCD	1/3" Sony SUPER HAD CCD
Sinyal Sistemi	PAL	PAL	PAL	PAL
IR Led Sayısı	12 High Power IR Led	35 HI IR Led	25 HI IR Led	24 IR Led
Gece Görüş Mesafesi	75-80 metre	45-50 metre	25-30 metre	10-15 metre
Piksel Sayısı	752 (H) x 582 (V)	752 (H) x 582 (V)	752 (H) x 582 (V)	752 (H) x 582 (V)
Çözünürlük	480 TV Lines	480 TV Lines	480 TV Lines	480 TV Lines
Işık Oranı	0Lux / F 1.2	0Lux / F 1.2	0Lux / F 1.2	0Lux / F 1.2
Lens	8 mm	8 mm	6 mm	3,6 mm
Shutter Hızı	1/50(1/60) 1/100,000sn	1/50(1/60) 1/100,000sn	1/50(1/60) 1/100,000sn	1/50(1/60) 1/100,000sn
Video Çıkışı	1.0Vp-p 75 Ohm	1.0Vp-p 75 Ohm	1.0Vp-p 75 Ohm	1.0Vp-p 75 Ohm
Güç İhtiyacı	AC 220V	DC 12V	DC 12V	DC 12V
Çalışma Isısı	-20°C + 50°C	-20°C + 50°C	-20°C + 50°C	-10°C + 50°C
S / N Oranı	48 dB'den fazla (AGC kapalı iken)	48 dB'den fazla (AGC kapalı iken)	48 dB'den fazla (AGC kapalı iken)	48 dB'den fazla (AGC kapalı iken)
Çalışma Nem Oranı	%40 ~ %90	%40 ~ %90	%40 ~ %90	%40 ~ %90
BLC	Otomatik	Otomatik	Otomatik	Otomatik
AGC	Otomatik	Otomatik	Otomatik	Otomatik
Gama Değeri	0,45	0,45	0,45	0,45
Dahili Senkronizasyon	Var	Var	Var	Var
Güç Tüketimi	250 mA / 1000 mA (Led Açık)	250 mA / 1000 mA (Led Açık)	250 mA / 750 mA (Led Açık)	250 mA / 500 mA (Led Açık)
Montaj Aparatı	Metal Ayak, Vida, Dubel	Metal Ayak, Vida, Dubel	Metal Ayak, Vida, Dubel	Metal Ayak, Vida, Dubel
Dayanıklılık Standardı	IP 66	IP 66	IP 66	IP 66
Ağırlık	2080 gr.	920 gr.	660 gr.	313 gr.



Türkiye'nin Güvenlik Çözümleri